# NSN 5930-00-259-9597

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-9597

# Thread Class:

2a single mounting facility

### Thread Length:

0.375 inches single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

1.562 inches

#### First Flat Length:

0.125 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

2.000 inches single actuator

#### **Overall Diameter:**

1.250 inches

#### Individual Section Quantity:

1

#### Knob Manufacturer Code:

76055

# Knob Manufacturer Part Number:

366

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

3 single section front

#### **Throw Quantity:**

4 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Features Provided:**

Actuator knob and metallic inclosure

#### **Thread Size:**

0.375 inches single mounting facility

## Contact Voltage Rating In Volts:

300.0 dc at sea level

#### **Rotor Through Connection Quantity:**

3 single section

#### Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, square single actuator

# NSN 5930-00-259-9597

Rotary Switch - Page 2 of 2



Square Shaft Size: 0.218 inches single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Contact Load Current Rating:** 20.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Snap or line **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No

# Fiig:

A052b0