## NSN 5930-00-259-9617



Sensitive Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-00-259-9617 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Vaportight **Actuator Style:** Round **Actuator Free Position Height:** 1.859 inches **Housing Height:** 2.547 inches **Housing Length:** 3.656 inches **Housing Width:** 2.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.812 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 2.750 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained single switch unit **Switch Release Force:** 12.0 ounces **Switch Actuating Force:** 48.0 ounces **Actuator Movement:** Between 0.078 pretravel inches and 0.187 overtravel inches and 0.004 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 700.000 milliamperes resistive dc and 2.000 amperes resistive ac **Terminal Type And Quantity:** 3 screw Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A053a0