NSN 5930-00-259-9624

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-9624

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| 1.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.875 inches |
| Overall Width: |
| 0.406 inches |
| Body Length: |
| 1.094 inches |
| Body Width: |
| 0.406 inches |
| Body Height: |
| 0.625 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.112 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.406 inches |
| Actuator Length: |
| 1.359 inches |
| Actuator Style: |
| Roller arm |
| Actuator Height: |
| 0.891 inches |
| Actuator Free Position Height: |
| 0.891 inches |
| Actuator Adapter Style: |
| Roller leaf |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 250.0 dc |
| End Application: |
| Mk 28, 5-inch 38 caliber twin gun mount" |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, three positions maintained single switch unit |

1.0 ounces

Switch Release Force:

NSN 5930-00-259-9624

Sensitive Switch - Page 2 of 2

A053a0



| Switch Actuating Force: |
|--|
| 5.0 ounces |
| Actuator Movement: |
| Between 0.188 pretravel inches and 0.062 overtravel inches and 0.078 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 700.000 milliamperes resistive dc and 2.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |