NSN 5930-00-259-9632

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-9632 **Body Style:** Hole mounted **Overall Length:** 1.938 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Overall Width:** 0.688 inches **Body Length:** 1.938 inches **Body Width:** 0.688 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches **Actuator Style:** Roller plunger **Actuator Free Position Height:** 1.250 inches **Actuator Roller Diameter:** 0.375 inches **Maximum Voltage Rating In Volts:** 600.0 ac **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 2.0 ounces **Switch Actuating Force:** 19.0 ounces **Actuator Movement:** Between 0.015 pretravel inches and 0.078 overtravel inches and 0.002 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 2.000 amperes resistive ac **Terminal Type And Quantity:** 3 screw Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5930-00-259-9632

Sensitive Switch - Page 2 of 2



Fiig:

A053a0