

View Online at <https://aerobasegroup.com/nsn/5930-00-260-4405>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.182 inches and 2.192 inches

Body Length:

Between 2.675 inches and 2.705 inches

Body Width:

Between 1.205 inches and 1.235 inches

Body Height:

Between 1.545 inches and 1.575 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.172 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.575 inches and 0.605 inches

Actuator Height:

0.906 inches

Actuator Free Position Height:

Between 1.151 inches and 1.161 inches

Maximum Voltage Rating In Volts:

125.0 ac

End Application:

6kidd class ddg, ticonderoga class cg (47), airborne mobile dir air spt ctl (2id), (02m july83), (an/uyq-3a), virginia class cgn (41), nimitz class cvn, oliver perry class ffg, spruance class dd (963), forrestal class cv, sturgeon class ssn (637).

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 0.094 pretravel inches and 0.188 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0