NSN 5930-00-261-6773

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-261-6773

| Body Style: | |
|---|-------------|
| Hole mounted | |
| Body Length: | |
| 1.340 inches | |
| Body Width: | |
| 0.520 inches | |
| Body Height: | |
| 2.090 inches | |
| Unthreaded Mounting Hole Diameter: | |
| 0.114 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | |
| 1.812 inches | |
| Actuator Style: | |
| Round | |
| Actuator Diameter: | |
| 0.250 inches | |
| Actuator Height: | |
| 0.375 inches | |
| Actuator Free Position Height: | |
| 0.375 inches | |
| Maximum Voltage Rating In Volts: | |
| 250.0 ac and 30.0 dc | |
| nclosure Type: | |
| Jninclosed | |
| Thready Qty Per Inch (tpi): | |
| 32 | |
| Thread Size: | |
| 0.138 inches | |
| Nonpile-up Contact Arrangement: | |
| 2 pole, double throw, one position momentary single switch unit | |
| Switch Release Force: | |
| 16.0 ounces | |
| Switch Actuating Force: | |
| 64.0 inch-ounces | |
| Actuator Movement: | |
| 0.172 pretravel inches and 0.250 overtravel inches and 0.010 differential inches | |
| Contact Load Current Rating At Maximum Rated Voltage: | |
| 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes in | nductive ac |
| Thread Series Designator: | |
| Unc | |
| Terminal Type And Quantity: | |
| | |

6 turret

NSN 5930-00-261-6773

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

