

View Online at <https://aerobasegroup.com/nsn/5930-00-261-7952>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

0.469 inches

Bushing Length:

Between 0.790 inches and 0.830 inches

Body Length:

0.930 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 0.190 inches and 0.220 inches

Actuator Roller Diameter:

Between 0.307 inches and 0.317 inches

Actuator Roller Width:

Between 0.056 inches and 0.066 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

90.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0