NSN 5930-00-261-8219

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-261-8219

Body Style:
Panel mounted
Overall Length:
2.690 inches
Overall Height:
0.800 inches
Overall Width:
0.800 inches
Body Width:
0.800 inches
Body Height:
0.800 inches
Case Material:
Metal
Actuator Length:
0.684 inches
Actuator Style:
Rectangular
Actuator Height:
0.360 inches
Actuator Width:
0.684 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.690 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 1.000 amperes inductive dc and 0.750 amperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes
inductive ac and 0.750 amperes lamp ac
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 tab, solder lug

Specification Data:

81349-mil-s-22885/56 government specification

Shelf Life:

N/a

NSN 5930-00-261-8219

Push Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A053a0