## NSN 5930-00-262-0559

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-00-262-0559



## **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.080 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

**Body Width:** 

0.750 inches

#### **Body Height:**

0.750 inches

#### Actuator Length:

#### 0.620 inches

Actuator Style:

#### Rectangular

Actuator Height:

0.100 inches

## Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

Green single actuator

#### **Actuator Inscription:**

Fwd/omni single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

2.996 inches

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

## **Features Provided:**

Horizontal split lens

## Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

# NSN 5930-00-262-0559

Push Switch - Page 2 of 2



## **Precious Material And Location:**

Contacts silver

## Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0