NSN 5930-00-262-0886

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-262-0886

Overall Length:
5.750 inches
Overall Height:
10.812 inches
Overall Width:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
3.000 inches
Shortest Horizontal Distance Between Mounting Centers:
1.750 inches
Longest Vertical Distance Between Mounting Centers:
4.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
3.2 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+1.00/+4.50 actuation point ounce and +1.00/+4.50 deactuation point ounce
Contact Adjustment Type:
External deactuation point shaft and external actuation point shaft
Contact Voltage Rating In Volts:

Pressure Connector Type:

550.0 ac at sea level first voltage

Plain, threaded internal single connection

NSN 5930-00-262-0886

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0