NSN 5930-00-262-0889

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5930-00-262-0669
Thread Class:
2a and 2b
Body Style:
Hole mount
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.796 inches and 1.828 inches
Bushing Length:
1.660 inches
Body Length:
1.988 inches
Body Width:
0.858 inches
Body Height:
1.360 inches
Actuator Style:
Round
Actuator Diameter:
Between 0.672 inches and 0.704 inches
Actuator Height:
0.910 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Bracket
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, momentary action single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
750.000 milliamperes inductive dc
Test Data Document:
81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf
Terminal Type And Quantity:
4 screw

N/a

Shelf Life:

NSN 5930-00-262-0889

Push Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A053a0