

View Online at <https://aerobasegroup.com/nsn/5930-00-263-0730>

**Overall Length:**

4.906 inches

**Body Diameter:**

Between 0.618 inches and 0.625 inches

**Body Length:**

3.594 inches

**Overall Diameter:**

1.750 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.192 inches and 0.195 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 1.079 inches and 1.085 inches

**Shortest Horizontal Distance Between Mounting Centers:**

Between 0.536 inches and 0.546 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 0.620 inches and 0.630 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -459.4 degrees fahrenheit and 1500.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

6.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+200.00/+450.00 actuation point degrees fahrenheit and +200.00/+450.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

10.00 differential point degrees fahrenheit and 350.00 actuation point degrees fahrenheit and 340.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

230.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0