

View Online at <https://aerobasegroup.com/nsn/5930-00-263-0730>

Overall Length:

4.906 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.594 inches

Overall Diameter:

1.750 inches

Unthreaded Mounting Hole Diameter:

Between 0.192 inches and 0.195 inches

Longest Horizontal Distance Between Mounting Centers:

Between 1.079 inches and 1.085 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.536 inches and 0.546 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.620 inches and 0.630 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -459.4 degrees fahrenheit and 1500.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

6.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+200.00/+450.00 actuation point degrees fahrenheit and +200.00/+450.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

10.00 differential point degrees fahrenheit and 350.00 actuation point degrees fahrenheit and 340.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0