## NSN 5930-00-263-2200

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted

Dustproof

1.000 inches

Body Length:
1.940 inches

Body Width:
0.687 inches

Body Height:



View Online at https://aerobasegroup.com/nsn/5930-00-263-2200

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

0.875 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
1.290 inches
Actuator Style:
Leaf
Actuator Width:
0.190 inches
Actuator Free Position Height:
0.693 inches
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, three positions maintained single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 10.0 ounces and 22.0 ounces
Actuator Movement:
Between 0.010 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
25.000 amperes resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac
Terminal Type And Quantity:
3 screw

## NSN 5930-00-263-2200

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0