NSN 5930-00-263-2362

Toggle Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-263-2362

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.812 inches
Body Length:
1.844 inches
Body Width:
1.375 inches
Body Height:
1.531 inches
Actuator Height:
0.875 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
3 pole, double throw, three positions maintained single switch unit
3 pole, double throw, three positions maintained single switch unit
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage:
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity:
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity: 9 tab w/screw
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity: 9 tab w/screw Shelf Life:
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity: 9 tab w/screw Shelf Life: N/a
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity: 9 tab w/screw Shelf Life: N/a
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity: 9 tab w/screw Shelf Life: N/a Unit Of Measure:
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity: 9 tab w/screw Shelf Life: N/a Unit Of Measure: Demilitarization:
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity: 9 tab w/screw Shelf Life: N/a Unit Of Measure: Demilitarization: No
3 pole, double throw, three positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 25.000 amperes resistive dc and 20.000 amperes resistive ac Terminal Type And Quantity: 9 tab w/screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: