NSN 5930-00-263-2972

Thermostatic Switch - Page 1 of 2

240.0 ac at sea level first voltage



View Online at https://aerobasegroup.com/nsn/5930-00-263-2972

Overall Length:
3.360 inches
Overall Height:
2.638 inches
Overall Width:
1.000 inches
Body Length:
1.500 inches
Body Width:
1.000 inches
Body Height:
1.470 inches
Unthreaded Mounting Hole Diameter:
0.218 inches
Distance Between Mounting Facility Centers:
3.000 inches
Capillary Tube Length:
18.000 inches
Tempurature Sensing Element Type:
Capillary tube
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Capillary tube end seal connection
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
-17.30/+26.00 actuation point degrees fahrenheit and -17.30/+26.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:

NSN 5930-00-263-2972

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A048b0