

View Online at <https://aerobasegroup.com/nsn/5930-00-263-7847>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Width Between Flats:

0.188 inches single actuator

Hazardous Locations/environmental Protection:

Fungus proof and moisture resistant

Overall Length:

1.735 inches

Overall Height:

1.875 inches

Overall Width:

1.562 inches

First Flat Length:

0.188 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.047 inches single actuator

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Special Features:

One no. 6-32 thsd by 3/8 in. Deep hole in shaft

Precious Material And Location:

Contacts and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0