

View Online at <https://aerobasegroup.com/nsn/5930-00-264-3435>

Overall Length:

3.625 inches

Body Length:

3.000 inches

Overall Diameter:

4.063 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -20.0 degrees celsius and 60.0 degrees celsius

Mounting Method:

Threaded bushing

Thread Qty Per Inch (tpi):

14 single threaded bushing

Contact Action Stimulus:

Increase

Proof Pressure:

25.00 pounds per square inch

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.20/+1.00 actuation point inches of water and +0.20/+1.00 deactuation point inches of water

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

0.12 actuation point inches of water and 0.16 deactuation point inches of water and 0.04 differential point inches of water

Contact Voltage Rating In Volts:

460.0 ac at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0