## NSN 5930-00-264-3435

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-264-3435 **Overall Length:** 3.625 inches **Body Length:** 3.000 inches Overall Diameter: 4.063 inches **Pressure Switch Type:** Differential **Operating Tempurature Rating:** Between -20.0 degrees celsius and 60.0 degrees celsius **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 14 single threaded bushing **Contact Action Stimulus:** Increase **Proof Pressure:** 25.00 pounds per square inch **Thread Size:** 0.500 inches single threaded bushing **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Tab w/screw **Contact Load Current Rating:** 15.0 amperes resistive load single voltage **Contact Adjustability:** Deactuation point adjustable, preset and actuation point adjustable, preset **Contact Adjustment Range:** +0.20/+1.00 actuation point inches of water and +0.20/+1.00 deactuation point inches of water **Contact Adjustment Type:** Internal deactuation point screw and internal actuation point screw **Contact Stimulus Rating:** 0.12 actuation point inches of water and 0.16 deactuation point inches of water and 0.04 differential point inches of water **Contact Voltage Rating In Volts:** 460.0 ac at sea level single voltage Media For Which Designed: Liquid

Thread Series Designator: Npt single threaded bushing

**Style Designator:** 

Cylindrical

## NSN 5930-00-264-3435

Pressure Switch - Page 2 of 2



_			-		
C	hΔ	Iŧ.		.ife	
J			_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0