# NSN 5930-00-265-6270

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-265-6270

Body Style:

Hole mounted

**Actuator Style:** 

Roller plunger

**Actuator Free Position Height:** 

2.031 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.188 inches

Housing Height:

1.797 inches

Housing Length:

Between 2.605 inches and 2.645 inches

Housing Width:

Between 0.985 inches and 1.015 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 0.996 inches and 1.004 inches

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

#### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

#### Switch Actuating Force:

Between 16.0 ounces and 32.0 ounces

#### **Actuator Movement:**

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.030 differential inches

#### **Test Data Document:**

88044-an3218-1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unc

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

# NSN 5930-00-265-6270

Sensitive Switch - Page 2 of 2

**Fiig:** A053a0

