

View Online at <https://aerobasegroup.com/nsn/5930-00-265-6271>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.004 inches

Body Length:

2.625 inches

Body Width:

1.000 inches

Body Height:

1.109 inches

Unthreaded Mounting Hole Diameter:

Between 0.166 inches and 0.176 inches

Actuator Style:

Round

Actuator Diameter:

0.328 inches

Actuator Height:

1.062 inches

Actuator Free Position Height:

1.812 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thread Size:

0.750 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

Between 1.0 ounces and 2.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 10.000 amperes inductive dc and 25.000 amperes resistive ac and 10.000 amperes inductive ac and 10.000 amperes motor ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0