

View Online at <https://aerobasegroup.com/nsn/5930-00-265-6272>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.098 inches and 1.004 inches

Body Length:

2.625 inches

Body Width:

1.000 inches

Body Height:

1.169 inches

Unthreaded Mounting Hole Diameter:

Between 0.166 inches and 0.176 inches

Actuator Style:

Round

Actuator Diameter:

0.328 inches

Actuator Height:

1.062 inches

Actuator Free Position Height:

1.812 inches

End Application:

Uvirginia class cgn (41), wasp class lhd, cvn 68 class reactor fill zuxiliary system, spruance class dd (963), kidd class ddg, tarawa class lha, forrestal class cv, nimitz class cvn, supply class aoe, los angeles class ssn (688).

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

14

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Switch Actuating Force:

Between 1.0 ounces and 2.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive ac and 10.000 amperes motor ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0