## NSN 5930-00-268-1549

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-268-1549

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.375 inches single mounting facility

**Overall Length:** 

3.483 inches

**Overall Height:** 

1.875 inches

**Overall Width:** 

1.593 inches

First Flat Length:

0.250 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

1.047 inches single actuator

**Individual Section Quantity:** 

3

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round, v flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

500.0 milliamperes resistive load ac at sea level

**Precious Material And Location:** 

Contacts and rotor blade surfaces silver

**Precious Material:** 

Silver

## NSN 5930-00-268-1549

Rotary Switch - Page 2 of 2



Sty	ما	D	20	in	n	2	ŧ۸	r	
JLY	ı	יש	င၁	ıу	••	а	ιυ	ш	

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0