## NSN 5930-00-268-2827

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-268-2827

Overall Length:
5.453 inches
Overall Height:
2.906 inches
Overall Width:
4.453 inches
Capillary Tube Length:
96.000 inches
Bulb Length:
4.000 inches
Bulb Diameter:
0.875 inches
Longest Horizontal Distance Between Mounting Centers:
2.750 inches
Longest Vertical Distance Between Mounting Centers:
3.125 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket
Features Provided:
Tubing end seal connection
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained
2 pole, single throw, both positions maintained
2 pole, single throw, both positions maintained  Terminal Type:
2 pole, single throw, both positions maintained  Terminal Type:  Tab w/screw
2 pole, single throw, both positions maintained  Terminal Type:  Tab w/screw  Contact Load Current Rating:
2 pole, single throw, both positions maintained  Terminal Type:  Tab w/screw  Contact Load Current Rating:  4.6 amperes resistive load third voltage
2 pole, single throw, both positions maintained  Terminal Type:  Tab w/screw  Contact Load Current Rating:  4.6 amperes resistive load third voltage  Contact Adjustability:
2 pole, single throw, both positions maintained  Terminal Type:  Tab w/screw  Contact Load Current Rating:  4.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable
2 pole, single throw, both positions maintained  Terminal Type:  Tab w/screw  Contact Load Current Rating:  4.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range:

Shelf Life: N/a

**Special Features:** 

0.750 in. Pipe fitting connection

## NSN 5930-00-268-2827

Thermostatic Switch - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A048b0