

View Online at <https://aerobasegroup.com/nsn/5930-00-269-2890>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.437 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.830 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.210 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.370 inches single actuator

**Overall Diameter:**

1.150 inches

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

8 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from contact position 1 single actuator

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0