

View Online at <https://aerobasegroup.com/nsn/5930-00-269-3301>

Overall Length:

5.656 inches

Overall Height:

5.297 inches

Overall Width:

2.156 inches

Mounting Slot Width:

0.203 inches

Body Height:

3.250 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Capillary Tube Length:

72.000 inches

Bulb Length:

6.750 inches

Bulb Diameter:

0.688 inches

Longest Horizontal Distance Between Mounting Centers:

4.984 inches

Longest Vertical Distance Between Mounting Centers:

0.453 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Base and unthreaded hole and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+90.00 actuation point degrees fahrenheit and +50.00/+90.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob and external actuation point knob

Contact Voltage Rating In Volts:

240.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiq:

A048b0