NSN 5930-00-270-1095

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-270-1095
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.250 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
Natural single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
Between 2.850 inches and 3.150 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes
inductive ac and 1 000 amperes lamp ac

Precious Material And Location:Contacts silver

NSN 5930-00-270-1095

Push Switch - Page 2 of 2



Terminal	Type	And	Quantity:
I CI IIIIIIIII	i ypc	Alla	Qualitity.

1 socket, integrated wire termination

Specification Data:

82918-37-1059-6 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0