

View Online at <https://aerobasegroup.com/nsn/5930-00-270-1686>

**Body Style:**

Bushing mount

**Bushing Length:**

Between 0.275 inches and 0.285 inches

**Body Length:**

Between 0.495 inches and 0.505 inches

**Body Width:**

Between 0.440 inches and 0.460 inches

**Body Height:**

Between 0.340 inches and 0.360 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.103 inches and 0.109 inches

**Actuator Height:**

Between 0.257 inches and 0.287 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

28.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

180.000 milliamperes resistive dc and 180.000 milliamperes resistive ac

**Special Features:**

Unthreadedbushing; printed circuit board mtd

**Terminal Type And Quantity:**

6 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0