

View Online at <https://aerobasegroup.com/nsn/5930-00-270-1703>

Thread Class:

2a single mounting facility

Thread Length:

0.188 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.688 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.813 inches single actuator

Overall Diameter:

0.719 inches

Individual Section Quantity:

2

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+2.200 inch-pounds single actuator

Contact Load Current Rating:

20.0 milliamperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0