

View Online at <https://aerobasegroup.com/nsn/5930-00-270-1706>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

0.469 inches

Bushing Length:

Between 1.750 inches and 1.810 inches

Body Length:

Between 0.340 inches and 0.400 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.148 inches and 0.158 inches

Actuator Height:

Between 0.145 inches and 0.175 inches

Actuator Free Position Height:

Between 0.145 inches and 0.175 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

104.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0