

View Online at <https://aerobasegroup.com/nsn/5930-00-270-3028>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Case Material:**

Metal

**Actuator Length:**

1.500 inches

**Actuator Style:**

Nonadjustable arm

**Actuator Height:**

0.675 inches

**Actuator Width:**

Between 0.255 inches and 0.275 inches

**Housing Height:**

2.250 inches

**Housing Length:**

2.812 inches

**Housing Width:**

1.125 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.875 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.437 inches

**Maximum Voltage Rating In Volts:**

240.0 ac and 28.0 dc

**End Application:**

Aircraft, stratolifter c-135; aircraft, (ac-130h, mc-130h, ec-130e,

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

48.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

24.0 ounces

**Actuator Movement:**

Between 44.0 pretravel degrees and 55.0 overtravel degrees and 57.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 500.000 milliamperes inductive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0