

View Online at <https://aerobasegroup.com/nsn/5930-00-270-3028>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Case Material:

Metal

Actuator Length:

1.500 inches

Actuator Style:

Nonadjustable arm

Actuator Height:

0.675 inches

Actuator Width:

Between 0.255 inches and 0.275 inches

Housing Height:

2.250 inches

Housing Length:

2.812 inches

Housing Width:

1.125 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.875 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.437 inches

Maximum Voltage Rating In Volts:

240.0 ac and 28.0 dc

End Application:

Aircraft, stratolifter c-135; aircraft, (ac-130h, mc-130h, ec-130e,

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

48.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

24.0 ounces

Actuator Movement:

Between 44.0 pretravel degrees and 55.0 overtravel degrees and 57.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 500.000 milliamperes inductive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0