NSN 5930-00-270-4805

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-270-4805 **Thread Class:** 2b single pressure connection **Inside Diameter:** 0.438 inches single connection Thread Length: 0.500 inches single pressure connection **Hazardous Locations/environmental Protection:** General purpose-nema type 1 **Overall Length:** 5.750 inches **Overall Height:** 10.812 inches **Overall Width:** 3.000 inches **Body Length:** 4.875 inches **Body Height:** 10.312 inches **Unthreaded Mounting Hole Diameter:** 0.375 inches **Longest Horizontal Distance Between Mounting Centers:** 3.000 inches **Shortest Horizontal Distance Between Mounting Centers:** 1.500 inches **Longest Vertical Distance Between Mounting Centers:** 4.250 inches **Pressure Switch Type: Operating Tempurature Rating:** Between -30.0 degrees fahrenheit and 580.0 degrees fahrenheit **Mounting Method:** Bracket and unthreaded hole **Features Provided:** Electrical access port Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Proof Pressure:**

3600.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

NSN 5930-00-270-4805Pressure Switch - Page 2 of 2



Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
4.0 amperes resistive load third voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+250.00/+3000.00 actuation point pounds per square inch and +210.00/+2920.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal actuation point hex nut with scale and internal deactuation point hex nut with scale
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Pressure Connector Type:
Plain, threaded internal single connection
Special Features:
Phosphor bronze housing for oxygen service
Media For Which Designed:
Gas
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A048b0