

View Online at <https://aerobasegroup.com/nsn/5930-00-270-4962>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

6.500 inches

**Overall Height:**

2.750 inches

**Overall Width:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches single mounting facility and 0.410 inches single mounting facility

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

3.781 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.781 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

60.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0