

View Online at <https://aerobasegroup.com/nsn/5930-00-270-7926>

Thread Length:

1.000 inches single pressure connection

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

3.000 inches

Outside Diameter:

0.250 inches single connection

Body Diameter:

1.875 inches

Body Length:

1.625 inches

Overall Diameter:

2.000 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.875 inches

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Threaded stud

Contact Load Current Rating:

10.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+50.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

10.00 deactuation point pounds per square inch and 1.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0