## NSN 5930-00-270-7926

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-270-7926

Thread	Length:
--------	---------

1.000 inches single pressure connection

**Hazardous Locations/environmental Protection:** 

Dustproof and watertight

**Overall Length:** 

3.000 inches

**Outside Diameter:** 

0.250 inches single connection

**Body Diameter:** 

1.875 inches

**Body Length:** 

1.625 inches

**Overall Diameter:** 

2.000 inches

**Pressure Switch Type:** 

Gage

Width Across Flats:

0.875 inches

**Mounting Method:** 

Clamp

Thready Qty Per Inch (tpi):

18 single pressure connection

**Contact Action Stimulus:** 

Increase

**Thread Size:** 

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally closed, momentary action

**Terminal Type:** 

Threaded stud

**Contact Load Current Rating:** 

10.0 amperes resistive load second voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point adjustable, preset

**Contact Adjustment Range:** 

+0.00/+50.00 actuation point pounds per square inch

**Contact Adjustment Type:** 

Internal actuation point screw

**Contact Stimulus Rating:** 

10.00 deactuation point pounds per square inch and 1.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level second voltage

## NSN 5930-00-270-7926

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded external single connection
Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0