

View Online at <https://aerobasegroup.com/nsn/5930-00-272-1229>

Overall Length:

4.938 inches

Overall Height:

1.375 inches

Overall Width:

0.875 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.594 inches

Unthreaded Mounting Hole Diameter:

0.144 inches

Longest Horizontal Distance Between Mounting Centers:

0.500 inches

Longest Vertical Distance Between Mounting Centers:

1.000 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 510.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Tamper proof cap

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-100.00/+600.00 actuation point degrees fahrenheit and -100.00/+600.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

410.00 actuation point degrees fahrenheit and 400.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A048b0