

View Online at <https://aerobasegroup.com/nsn/5930-00-272-1236>

**Overall Length:**

4.938 inches

**Overall Height:**

0.875 inches

**Overall Width:**

1.375 inches

**Body Diameter:**

Between 0.618 inches and 0.625 inches

**Body Length:**

3.594 inches

**Unthreaded Mounting Hole Diameter:**

0.144 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.000 inches

**Longest Vertical Distance Between Mounting Centers:**

0.500 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -100.0 degrees fahrenheit and 590.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Tamper proof cap

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+100.00/+600.00 actuation point degrees fahrenheit and -100.00/+600.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

490.00 actuation point degrees fahrenheit and 485.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level fourth voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A048b0