NSN 5930-00-272-1300

Thermostatic Switch - Page 1 of 2

Gas or liquid



View Online at https://aerobasegroup.com/nsn/5930-00-272-1300

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.938 inches
Body Diameter:
0.622 inches
Body Length:
3.594 inches
Overall Diameter:
1.750 inches
Unthreaded Mounting Hole Diameter:
0.169 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Facility Circle Radius:
1.250 inches
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Three position circular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+100.00/+600.00 actuation point degrees fahrenheit and +100.00/+600.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:
160.00 actuation point degrees fahrenheit and 15.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level fourth voltage
Media For Which Designed:

NSN 5930-00-272-1300

Thermostatic Switch - Page 2 of 2



•	_		
Style	1)69	เตทร	ntor.
01,10	-	9	

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0