

View Online at <https://aerobasegroup.com/nsn/5930-00-272-1338>

**Body Style:**

Hole mounted

**Overall Length:**

1.938 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Overall Width:**

0.688 inches

**Body Length:**

1.938 inches

**Body Width:**

0.688 inches

**Body Height:**

0.844 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.094 inches

**Actuator Height:**

0.047 inches

**Actuator Free Position Height:**

0.641 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 250.0 dc

**End Application:**

Tarawa class lha, whidbey island class lsd, iwo jima class lph, blue ridge class lcc-19, virginia class cgn (41).

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

10.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

Between 14.0 ounces and 22.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.010 overtravel inches and 0.002 differential inches and 0.007 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0