## NSN 5930-00-273-9443

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-273-9443

Body Style:					
Panel mounted					
Hazardous Locations/environmental Protection:					
Explosion proof and humidity resistant					
Overall Length:					
3.096 inches					
Overall Height:					
0.750 inches					
Overall Width:					
0.750 inches					
Body Width:					
0.750 inches					
Body Height:					
0.750 inches					
Case Material:					
Metal					
Actuator Length:					
0.620 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.100 inches					
Actuator Width:					
0.620 inches					
Actuator Color:					
White and white single actuator					
Illuminated Actuator Color:					
Green and amber single actuator					
Actuator Inscription:					
In pr; st by single actuator					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
Mounting Surface To Terminal End Distance:					
2.996 inches					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Features Provided:					
Horizontal split lens					
Nonpile-up Contact Arrangement:					
2 pole, double throw, one position momentary single switch unit					

## NSN 5930-00-273-9443

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

D۳	acione	Matoria	I And	Location:
71	ecious	wateria	II Ana	Location.

Contacts silver

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0