

View Online at <https://aerobasegroup.com/nsn/5930-00-273-9626>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Actuator Length:**

0.875 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

0.620 inches

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.250 inches

**Housing Height:**

2.250 inches

**Housing Length:**

4.250 inches

**Housing Width:**

1.625 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.344 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.156 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 600.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

50.0 inch-ounces

**Switch Actuating Force:**

45.0 inch-ounces

**Actuator Movement:**

11.0 pretravel degrees and 75.0 overtravel degrees and 5.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 5.000 amperes resistive ac

**Precious Material And Location:**

Contacts rhodium

**Terminal Type And Quantity:**

4 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0