

View Online at <https://aerobasegroup.com/nsn/5930-00-273-9626>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Actuator Length:

0.875 inches

Actuator Style:

Roller arm

Actuator Height:

0.620 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

2.250 inches

Housing Length:

4.250 inches

Housing Width:

1.625 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

50.0 inch-ounces

Switch Actuating Force:

45.0 inch-ounces

Actuator Movement:

11.0 pretravel degrees and 75.0 overtravel degrees and 5.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts rhodium

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0