

View Online at <https://aerobasegroup.com/nsn/5930-00-274-7167>

Thread Class:

2a single pressure connection

Thread Length:

0.479 inches single pressure connection

Overall Length:

2.046 inches

Outside Diameter:

0.375 inches single connection

Body Length:

1.156 inches

Overall Diameter:

1.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -55.0 degrees celsius and 75.0 degrees celsius

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

24 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

40.00 pounds per square inch

Thread Size:

0.375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire loop

Contact Load Current Rating:

3.5 amperes resistive load single voltage and 1.7 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

22.00 actuation point pounds per square inch and 19.00 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0