

View Online at <https://aerobasegroup.com/nsn/5930-00-275-0466>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

0.875 inches

Body Width:

0.400 inches

Body Height:

1.230 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Actuator Length:

0.679 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.870 inches

Actuator Roller Diameter:

0.312 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

Between 0.135 pretravel inches and 0.040 overtravel inches and 0.058 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

8.000 amperes resistive dc and 7.500 amperes inductive dc and 8.000 amperes resistive ac

Special Features:

Lh actuator

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0