## NSN 5930-00-275-1262

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-275-1262 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length:** 1.500 inches **Overall Height:** 1.688 inches **Overall Width:** 0.500 inches **Bushing Length:** 0.312 inches **Body Length:** 1.500 inches **Body Width:** 0.500 inches **Body Height:** 0.938 inches **Case Material:** Metal **Actuator Diameter:** 0.402 inches **Actuator Height:** 0.750 inches **Maximum Voltage Rating In Volts:** 120.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi):

**-**. . . .

Thread Size:

0.625 inches

**Nonpile-up Contact Arrangement:** 

1 two circuit, double break/double make, both positions maintained single switch unit

## **Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 7.000 amperes inductive dc and 4.000 amperes lamp dc and 10.000 amperes motor dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac and 3.000 amperes motor ac

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

4 tab, solder lug

## NSN 5930-00-275-1262

Push Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0