

View Online at <https://aerobasegroup.com/nsn/5930-00-275-3108>

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mils6744 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0