## NSN 5930-00-275-8091

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-275-8091

#### Thread Length:

0.437 inches single mounting facility

#### **Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:** 

1.899 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.125 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.437 inches single actuator

**Overall Diameter:** 

1.000 inches

#### **Individual Section Quantity:**

1

### **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section rear

**Throw Quantity:** 

3 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

#### **Contact Switching Action:**

Makes before breaks single section rear

## **Switch Actuator Positioning Increment:**

36.0 degrees single actuator

#### **Contact Load Current Rating:**

3.0 amperes resistive load ac at sea level

#### **Special Features:**

Nonturn device type tab

# NSN 5930-00-275-8091

Rotary Switch - Page 2 of 2



Sty				

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0