# NSN 5930-00-275-8091

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-275-8091

### **Thread Length:**

0.437 inches single mounting facility

## Hazardous Locations/environmental Protection:

Moisture resistant

## **Overall Length:**

1.899 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.125 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.437 inches single actuator

#### **Overall Diameter:**

1.000 inches

#### Individual Section Quantity:

1

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 single section rear

#### Throw Quantity:

3 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

115.0 ac at sea level

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Makes before breaks single section rear

## Switch Actuator Positioning Increment:

36.0 degrees single actuator

## **Contact Load Current Rating:**

3.0 amperes resistive load ac at sea level

**Special Features:** 

Nonturn device type tab

# NSN 5930-00-275-8091

Rotary Switch - Page 2 of 2

Style Designator:

Circular wafer, bushing mount

# Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

