## NSN 5930-00-276-3210

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-276-3210

**Thread Class:** 2a single mounting facility Thread Length: 0.438 inches single mounting facility **Overall Length:** 2.688 inches **Overall Height:** 1.375 inches **Overall Width:** 1.297 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.938 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 each section rear **Throw Quantity:** 9 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-276-3210

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

70.0 milliamperes resistive load ac at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A052b0